



1802-EPD

TELEPHONE ENTRY SYSTEM



BEST SUITED FOR APPLICATIONS OF UP TO 100 RESIDENTS AND WHERE SPACE IS LIMITED



flush mount

surface mount

- Slim design for applications with limited space. Surface or flush mount styles available
- Visitors use the phone system to communicate with a resident who can grant or deny access via their own touch-tone telephone
- Programmable directory codes can be set from 1 to 4 digits
- Provides service for up to 100 residents
- 2 year limited factory warranty



modular design
makes installation and service easy



dtmf tone output
useable with PBX, KSU and telephone systems with auto-attendants





built-in display
resident directory



large buttons
A to Z scroll and one touch CALL buttons for quick and easy operation

1802-EPD TELEPHONE ENTRY SYSTEM



1802-EPD Surface

6.5" W x 12" H x 5" D @ top 3.25"
(16.5cm W x 30.4cm H x 12.7cm D)

1802-EPD Flush

8.375" W x 14" H x 3.25" D
(30.4cm W x 34.3cm H x 6.35cm D)

1802-EPD	PHONE # MEMORY	ENTRY CODES	DEVICE CODES	RELAYS	DIRECTORY	ELEVATOR CONTROL	PROGRAMMING OPTIONS	OPTIONS	TRANSACTION BUFFER
Surface Mount	100	100 (4-digit) 6 (5-digit)	N/A	2	Single-Line LCD Display	-	System Keypad or Touch-Tone Telephone	Handset Kit	-
Flush Mount	100	100 (4-digit) 6 (5-digit)	N/A	2	Single-Line LCD Display	-	System Keypad or Touch-Tone Telephone		-

Technical Features

Mechanical

- Stainless steel faceplate
- Galvanized steel sub-plate
- Metal keypad
- Offset speaker holes for protection
- Hands free voice operation (Optional handset available on surface mount style only)
- Built-in postal lock provision
- Surface and Flush mounting styles
- NEMA 4x rated enclosure

Programming Methods

User programmable welcome and instruction messages. Up to 48 characters each
All programming is from the system keypad

Electrical

- Single-line 16 character LCD display
- 16 VAC (power transformer included)
- Full Duplex voice communication
- Stores up to 100 phone numbers, 15 area codes
- Programmable directory codes (1 to 4 digits)
- 10 & 11 digit dialing capability
- DTMF tone output allows for use with KSU, PBX and auto-attendant type phone systems
- Four-digit entry codes (100)
- Five-digit entry codes (6)
- Built-in clock calendar
- Time clock has its own backup power source
- Entry code time zones
- Hold open time zones (4)
- Flash entry codes
- LCD display for programming assistance
- Two relays to control two entry points

Miscellaneous

- Environmental: 10°F to 145°F (-12°C to 62°C)
- LCD heater kit (P/N 2600-582) recommended when temperatures routinely fall below 10°F (-12°C)
- ADA Compliant handset kit (P/N 1807-012) available on surface mount only
- Camera Ready: Optional B&W or Color CCTV camera*
*may require additional CCTV equipment
- Shipping weight approximately 15-20 Lbs (6.8-9 kg)



FCC (US) DUF6VT-12874-0T-0
DOC (CAN) 1736 4507 A



Access Control Solutions since 1948

Distributed by:

MEMBER:



DOORKING, INC.

120 Glasgow Avenue, Inglewood, California 90301 U.S.A.
Tel: 310-645-0023 FAX: 310-641-1586 www.doorking.com

© 2012 All Rights Reserved. Product specifications may change without notice.
Rev. 9/12